Premium quality primer, sealer and bonding agent, rapid drying with high bond strength.

USES: Use with plaster, cement, timber, gypsum wall boards and paper. Properties as an adhesive include fast drying. Also a readily dilutable primer for sealing applications or can be added to cement and plaster to improve adhesion and cure. Can be used as a rendering key coat, admixture or dust sealer, and also as an adhesive as long as one surface is porous.

APPLICATION & MIXING RATIO: Ensure all surfaces are clean, dry and free from dust or grease. Remove all loose material and ensure underlying material is strong enough to take the weight or load to be applied. If required, a sealing coat should be applied and allowed to dry thoroughly before use. See technical data sheet for further application information.

- Suction control for plastering on porous surfaces: Primer coat: dilute 1 part PVA Bond with 4 parts water, or 5 parts guaging water for plaster, allow coat to dry before continuing. A 5L primer mix will cover approx. 115m^2. Bonding coat: Apply PVA Bond undiluted. Apply fresh plaster whilst PVA is still tacky. A 5L bond mix will cover approx. 45m^2.
- Plastering on non-porous surfaces: Apply PVA Bond undiluted, Apply fresh plaster whilst PVA is still tacky.
- Dust-proofing: Dilute 1 part PVA Bond with 4 parts water, ensure dry before continuing.
- Admixture: Will improve workability and adhesion of plasters and cements. Cement: 1 part PVA Bond to 1 part gauging water. Plaster: 1 part PVA Bond to 5 parts gauging water.
- Adhesive: Apply to one surface undiluted and whilst wet bring surfaces together and clamp until dry.

HEALTH & SAFETY: Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benziso-thiazol-3(2H)-one; 1,2 benzisothiazolin3-one. May produce an allergic reaction. Safety data sheet available on request. Do not ingest. Wear gloves, wash splashes off skin with soap and water. If product enters eyes, irrigate immediately with clean, cold water. Keep out of reach of children. Some people are more sensitive to chemical products than others; if irritation occurs discontinue use.

LIMITATIONS: Do not use in areas subject to constant water immersion or where permanent dampness is likely. Not recommended for use on new cement when cement has not fully dried. Do not use at surface temperatures below +5^{0}C.

CLEANING OF TOOLS: Clean with soapy water.

STORAGE: In cool, dry conditions between +5 and +25^{0}C. Protect from frost and direct sunlight. Use within 24 months from date of manufacture.

NOTE: General guidance only. It is the user's responsibility to check suitability. Always follow the instructions carefully. Our liability is limited to replacement or refund of cost of the product. Please scan the QR code to access and download all technical data for this product.

Head Office: Unit H4, Premier Way,
Lowfields Business Park, Elland, HX5 9HF.
T: 01422 315300. salesuk@bonditgroup.com.
www.bonditgroup.com.

EU Office: SISL (Bond It) Ireland Limited.
70 Sir John Rogerson's Quay, Dublin 2.
T: +353 1 960 9411.

An ASTRAL Limited Company.
Manufactured in the UK.

Product Code: **BDA021**
Size: **500ml** ∈ Colour: **White**

5 060021 361653 >

bond it

ALL PURPOSE

PVA BOND

ADHESIVE & SEALER

INTERIOR USE

RAPID DRYING

STRONG BOND

WHITE

PRIMES & SEALS POROUS SURFACES
IMPROVES PLASTER, CONCRETE & CEMENT MIXES
PHTHALATE-FREE FORMULATION
BS5270

500ml



ASP0823 V 10:25